

SWIMMING POOL HANDBOOK

COMPOSITE ARMOUR™ SWIMMING POOL





TABLE OF CONTENTS

IMPORTANT LETTER PLEASE READ	2
WARNING, NOTICE AND DISCLAIMER	3
DROWNING	4
PARALYSIS	4
FIRES AND BURNS	4
ELECTRICAL SHOCK AND ELECTROCUTION	4
SAFETY TIPS TO PREVENT DROWNING	5
DIVING AND JUMPING GUIDELINES	6
POOL SLIDE GUIDELINES	6
OTHER SAFETY GUIDELINES	
POOL FENCING.	6
THE BASICS OF POOL OPERATION	7
POOL CHEMISTRY	8
WATER BALANCE	8
pH	8
TOTAL ALKALINITY	9
THE RELATIONSHIP BETWEEN PH AND TOTAL ALKALINITY	9
CALCIUM	10
SANITISER	11
STABILISER	11
CHEMICAL ADDITIONS	11
DO NOT EMPTY YOUR SWIMMING POOL	
STANDPIPE / SUMP TUBE	12
DRAINAGE	
MODIFICATIONS / REPAIRS TO SWIMMING POOL	12
WINTERISING	12
LIFETIME STRUCTURAL WARRANTY	13
LIFETIME STRUCTURAL OSMOSIS WARRANTY	13
EXCLUSIONS TO LIFETIME STRUCTURAL WARRANTY	13
WARRANTY CLAIM	
DISCLAIMERS	
LIMITATIONS	14
TRANSFER OF WARRANTY	14
WATER TESTING RECORD TARI F	15



IMPORTANT LETTER PLEASE READ

PLEASE RETURN WARRANTY CARD IN ORDER TO HAVE A VALID LIFETIME STRUCTURAL WARRANTY

Congratulations on purchasing a Leisure Pools Composite Armour™ swimming pool.

Your Leisure Pools Composite Armour™ swimming pool has been manufactured with superior materials and under stringent quality control conditions to provide you with a quality product.

We have set out in this Handbook some important information that you should be aware of to protect and maintain your Leisure Pools Composite Armour™ swimming pool. Please read this Handbook and keep it in a safe place as a point of reference. If you maintain your Leisure Pools swimming pool correctly it will provide you with years of fun and enjoyment.

Your Leisure Pools Composite Armour™ swimming pool is covered by a Lifetime Structural Warranty and a Lifetime Structural Osmosis Warranty for the purchaser of the swimming pool. To preserve the Lifetime Warranty there are some basic steps that are set out in this Handbook that you need to undertake in order to maintain your Lifetime Structural Warranty (refer to the Lifetime Structural Warranty in this Handbook for the complete conditions applying to the Warranty).

Please ensure you fill out the online Warranty Form for your Leisure Pools swimming pool. For you to have a valid Lifetime Structural Warranty you must submit this online within 6 months from receiving the email request. Once you have submitted the online form you will receive a confirmation email.

In the online form we have included a section for you to provide feedback or a recommendation about the company who installed your Leisure Pools swimming pool. We welcome all feedback and thank you for sharing your experience.

We have also enclosed a Certificate of Recommendation. We would ask that if you are happy with your Leisure Pools swimming pool that you complete the Certificate of Recommendation and return to us together with the Warranty Card in the stamp self-addressed envelope.

We wish you and your family both good health and happiness and hope that your Leisure Pools swimming pool provides you with many years of family fun and enjoyment.

Kindest Regards
The Team at Leisure Pools

WARNING, NOTICE AND DISCLAIMER

Leisure Pools provides the following warning:

- In no event shall the manufacturer or any entity affiliated with Leisure Pools be held liable for damage
 to property, lost profits, injury, injury to goodwill and or any other special incidental or consequential
 damages resulting from advice or instructions contained in this Handbook.
- Always refer to the Owner Instructions provided to you by the supplier for the correct operating
 procedures of all pool equipment, supplies and the use of chemicals.

Leisure Pools provides the following Notice and Disclaimer to customers of the non-relationship between Dealer and Manufacturer hereinafter referred to as "Leisure Pools":

- This notice and disclaimer is made to all retail customers and buyers of products manufactured by Leisure Pools. You are by this notice advised that independent dealers and dealerships sell products manufactured by Leisure Pools.
- Each dealer is an independent business, which is completely separate from the manufacturer of Leisure Pools. Each dealer is an independent contractor, and no dealer is an owner, agent (in fact or law), or employee of Leisure Pools, the manufacturer.
- Leisure Pools, the manufacturer, hereby disclaims any liability for any intentional or negligent act by
 any Leisure Pools dealer or dealership or any damage to any Leisure Pool caused by an act of any dealer
 or dealership. Leisure Pools will not be responsible or liable for any damages caused by any dealer or
 dealership.
- As part of your Leisure Pools purchase you may have also purchased other pool products such as pool
 equipment, pool covers etc. Leisure Pools does not manufacture these products. Please refer to the
 manufacturers warranty and user guides for more information.
- Leisure Pools, as the manufacturer, offers a separate warranty to all customers and buyers of Leisure Pools. That warranty offered by Leisure Pools, the manufacturer, is separate and apart from other or additional warranty or guarantee offered by any dealer or dealership.
- Any statement in any advertisement, literature, brochure, or website should not be interpreted or
 construed to expressly or impliedly create any relationship between Leisure Pools and any dealer or
 dealership contrary to this notice and disclaimer.

IMPORTANT INFORMATION

SAFETY FIRST

Serious injury and death can result from unsafe use of pools, pool equipment and associated products.

The following are some examples:

DROWNING

Drowning is a major cause of deaths each year. The water depth of any pool is enough for drowning to occur. Drowning is a serious risk and should be given the full attention of the owner of the swimming pool to ensure that suitable safeguards are put in place to prevent this serious risk of death from occurring.

PARALYSIS

Diving or sliding, alcohol consumption, horseplay, or roughhousing in and around swimming pools may lead to serious neck and spinal injuries including paralysis, in the form of quadriplegia or paraplegia. Inform family and guests who will use your pool of the safety rules you have established.

FIRES AND BURNS

The chemicals needed to maintain your water chemistry are potentially harmful when stored or used improperly. If mixed with other chemicals, explosion and fire can occur. Read the labels on the chemical containers and follow manufacturers' instructions. Always store chemicals out of the reach of children.

ELECTRICAL SHOCK AND ELECTROCUTION

Water is an excellent conductor of electricity. Electrical shock or electrocution can occur in a pool if live electrical current flowing through appliances comes in contact with the water.

IMPORTANT: Establish safety rules for the use of your swimming pool and enforce them. Help ensure your family and guests are not victims of any of these unfortunate accidents.

SAFETY FIRST

SAFETY TIPS TO PREVENT DROWNING

The following is a list of Safety Tips to help in preventing a drowning. Please also refer to various Government and Association websites that provide extensive information on safety tips to prevent drowning.

- Ensure your pool complies with all relevant laws and regulations.
- Always watch your children and never leave them unattended.
- Do not allow anyone of any age to swim alone no matter how experienced they are as swimmers. Accidents can occur in a swimming pool and even the most experienced swimmers are at risk of drowning.
- Always have a phone close by, as it will provide quicker access to a medical facility in case of an emergency.
- If a child is missing, check the pool first as every second can count.
- Share safety instructions with family, friends and neighbours.
- Learn to swim and teach your children and other family members how to swim.
- Know how to perform CPR on children and adults.
- Understand the basics of life-saving so that you can assist in a pool emergency.
- Install a swimming pool compliant fence around the perimeter of the pool and/or spa.
- Use self-closing and self-latching gates on the fence.
- Install a door alarm from the house to the pool area.
- Make certain that all doors leading from the house to the pool area have a self-closing and/or self-latching mechanism above the reach of small children to protect against all unauthorised entry and use.
- Maintain pool and spa covers in working order.
- Ensure the pool and spa you use have compliant drain covers.
- Have life-saving equipment such as life rings or reaching poles available for use.
- Do not rely on plastic inner tubes, inflatable armbands, or other toys to prevent drowning accidents.
- When the pool is not in use, the pool owner is responsible for safeguarding the pool.

SAFETY GUIDELINES FOR USING YOUR LEISURE POOLS SWIMMING POOL

DIVING AND JUMPING GUIDELINES

Leisure Pools swimming pools and spas are not designed as diving pools or pools to jump into. This means that each Leisure Pools swimming pool is not designed for users to dive or jump into. Instead, pre-moulded steps are designed into all swimming pools to enable access both in and out of the swimming pool.

Leisure Pools are designated as a non-diving or jumping pool and therefore no diving or jumping of any type should be performed in any Leisure Pool swimming pool or spa. Diving or jumping into the pool could result in serious injury, paralysis or death.

POOL SLIDE GUIDELINES

Leisure Pools swimming pools and spas are not designed for pool slides. This means that each Leisure Pools swimming pool is not designed for the installation and use of a pool slide. Installing a slide into a Leisure Pools swimming pool could result in serious injury, paralysis or death.

OTHER SAFETY GUIDELINES

- Uses of alcohol or drugs do not mix with swimming pool activities and could result in serious injury or death.
- Never allow anyone to use the swimming pool under the influence of alcohol or drugs.
- Have a complete first aid kit at the swimming pool and be able to understand how to properly use its' contents.
- Post a list of emergency telephone numbers by the phone nearest the swimming pool. The list should
 include the names and telephone numbers of the nearest physician, ambulance service, hospital, police
 and fire or rescue unit.
- At a minimum, one responsible person should be trained in artificial respiration and or cardiopulmonary resuscitation (CPR).

POOL FENCING

It is critical for everyone's safety that you are aware of your legal obligations in terms of fencing your swimming pool. In many jurisdictions, No water may go into a pool until it is properly fenced.

There are strict laws in relation to the fencing of swimming pools. It is critical that you investigate with your local Council or Authority regarding the fencing laws that apply to your location.

THE BASICS OF POOL OPERATION

Your Leisure Pools Composite Armour™ swimming pool (also known as a Fibre-Reinforced Composite Pool) will have a skimmer located on the side of the pool. The skimmer is the point at which water is drawn from the pool by the pump and is key to proper circulation. The skimmer is designed to trap floating debris from the water surface in a basket. The basket can be removed from the skimmer and emptied.

The skimmer basket will also trap debris that is vacuumed from the floor of the pool by a manual cleaning vacuum or some automatic pool cleaners. A plate is inserted into the skimmer over the basket in order to create a suction point for the manual cleaning vacuum or some automatic pool cleaners. You should check the skimmer basket regularly and empty debris from it, so as not to impede the operation of the pump.

Once through the skimmer, the water travels along the suction line to the pump itself. At this point, there is a basket built into the pump to trap any debris that managed to get through the skimmer basket. This is called the hair and lint basket and is designed to trap finer particles of debris. Again, this basket is removable and should be cleaned regularly. Please refer to the Pump Operation Manual for specific operation and maintenance instructions.

Water then passes into the filter for the filtration and removal of even finer particles from the water. Filters are generally sand type filters or cartridge type filters. Most filters have a pressure gauge built into the filter that will tell you when to clean the filter. The more clogged the filter becomes the higher the pressure will become, and this is normally indicated on the pressure gauge.

To clean a sand filter, simply turn off the pump and position the handle at the top of the filter to the backwash position. Turn the pump on and you will see the dirty water rushing out through the backwash line. Most filters have a sight glass where you can view this happening. Normally, backwashing for 3-4 minutes is sufficient. Turn the pump off and move the handle to rinse and run the pump for about 20 seconds. Again, turn the pump off and return the handle to the original filter position and turn the pump on again. Please don't wander off while you're backwashing because the water could quickly drop below the level of the skimmer box and run the pump dry. Please refer to the Manufacturer's Operation Manual for specific operation and maintenance instructions.

To clean a cartridge filter, the filter must be removed from its housing in order to clean it. Usually this requires undoing a clamp from the top of the filter and removing the lid. You can then extract the cartridge filter for cleaning. A hose is all you need to wash away the debris that is trapped in the folds of the cartridge filter. Sometimes it helps to slightly open the folds in the cartridge with your fingers to get the hose right in to thoroughly clean the cartridge. The pump must be off through the entire procedure. Once the cartridge filter is clean, re-assemble the cartridge filter and replace the lid and clamp. There will be some trapped air inside the filter housing. This can be expelled by opening an air bleed on the top of the lid. Turn the pump on and the air will hiss out of the air bleed. Continue until water spurts out and when this happens, tighten up the air bleed. You're back in business. Please refer to the Manufacturer's Operation Manual for specific operation and maintenance instructions.

The clean filtered water will now return to the pool via the return line, but first it will normally be sanitised. One of the most common systems is a salt chlorinator. The salt chlorinator cell is installed in the return line and produces chlorine from the salt water by means of electrolysis. Please refer to the Manufacturer's Operation Manual for specific operation and maintenance instructions. Other sanitising systems are also available. Please refer to these specific Manuals for operation and maintenance instructions.

The clean filtered sanitised water is now on the way back to the pool via the return line. The return line is usually divided, at this point, into the water returns to the pool via several return jets. It's a good idea to have one of these jets adjusted to move surface water toward the skimmer and one adjusted toward the floor to move any debris on the floor. Thus, the cycle is complete and if you run your filtration system the correct amount of time according to the size of the pool, usage and temperature conditions, you should have very few problems.

POOL CHEMISTRY

It is important to be aware that untreated or improperly treated pool water can be a health threat that could cause serious injury or death. Chemically balanced and sanitised water, on the other hand, will provide a healthy and visually appealing environment for you, your family and friends.

Pool water can be contaminated with algae and bacteria from a variety of sources, including wind, top-up water and swimmers. Controlling these influences is an ongoing requirement and involves:

- Chemically balancing the water to ensure it is neutral for swimmers, the Leisure Pools Composite Armour™ swimming pool itself and pool equipment;
- Sanitising the water to oxidize contaminants;
- Filtering the water to remove oxidized contaminants;
- Regular testing and balancing your water to ensure that all acceptable levels are being maintained.

WATER BALANCE

Your Leisure Pools swimming pool is a water container and the water it contains must be suitable for:

- Swimmers and pool users;
- Leisure Pools Composite Armour[™] swimming pool.

Balanced water means that its chemical demands have been met. If the chemical levels are too low, the water will aggressively seek the products it needs by attacking and damaging the pool surface and equipment.

At the other end of the scale, high chemical levels will precipitate from the water and damage the pool surface and equipment. Out of balance water can, therefore, cause expensive damage to your Leisure Pools Composite Armour™ swimming pool and equipment and may also inhibit the sanitation process. In simple terms, a scientific water balance program suggests that you should balance the following variables:

- pH
- Total Alkalinity
- Calcium Hardness

рΗ

pH is a measure of how acidic or alkaline the water is. The pH scale ranges from 0 to 14, with 7 being neutral. Values below 7 are acidic and values above 7 are alkaline.

With pool water, we are seeking a pH balance suitable to the pool users, the Leisure Pools Composite Armour™ swimming pool shell and the sanitiser used. Leisure Pools strictly recommends a pH level of between 7.2 and 7.4.

Topping up your pool, heavy rain, heavy bathing loads and chemical additions can all change the pH level of your pool water. pH must be kept within the operating range because if it is too high or too low it may:

- Create swimmer discomfort;
- Interfere with the sterilization action of your pool sanitiser;
- Damage your Leisure Pools Composite Armour™ swimming pool.

Regardless of the chlorine type or chlorinator process you use, any pH drift above 7.2 to 7.4 will inhibit the sanitising effect of your chlorine and damage your Leisure Pools Composite Armour™ swimming pool. In that regard, to maintain your Lifetime Structural Warranty on your Leisure Pools Composite Armour™ swimming pool, you must maintain a pH level of 7.2 to 7.4. You must keep a monthly written record of the levels in the pool to ensure you do not invalidate your Lifetime Structural Warranty.

TOTAL ALKALINITY

This is a measure of bicarbonates, carbonates and hydroxides in your water. The recommended range is 80 to 120 parts per million with 100 parts per million being ideal. In that regard, to maintain your Lifetime Structural Warranty on your Leisure Pools Composite Armour™ swimming pool, you must maintain the total alkalinity between 80 to 120 parts per million. You must keep a monthly written record of the levels in the pool to ensure you do not invalidate your Lifetime Structural Warranty.

Lower total alkalinity will lead to the water attacking the walls of the Leisure Pools Composite Armour™ swimming pool. Low levels will also cause the pH levels to be very unstable with small additions of chemicals resulting in major shifts in the pH values. Your total alkalinity can be changed in the following ways:

- Adding buffer to your pool water to raise the total alkalinity;
- Adding acid to your pool water to lower pH and will also lower total alkalinity;
- Adding water to your pool will change the total alkalinity depending upon the total alkalinity of the topup water.

THE RELATIONSHIP BETWEEN pH AND TOTAL ALKALINITY

Adding acid to a pool will lower the pH and Total Alkalinity. There is a relationship between these two chemical components and because of this; they need to be adjusted together. The levels you are seeking to maintain are:

- pH 7.2 to 7.4
- Total Alkalinity between 80 to 120 part per million
 (Note: The required levels stated are for standard salt water pools only and not for pools containing magnesium salt. Unlike a standard salt water pool, the magnesium salts will show up in a total calcium test. In a pool running magnesium salts you could easily find 70% of the total hardness attributed to the magnesium salts rather than the calcium. Allowance must be made for this when taking total hardness readings in pools running mineral salts which include magnesium).

Let's have a look at the relationship. Assume that the pH is ok but the total alkalinity is low. To raise the level, add "Buffer" (sodium bicarbonate) at the required rate. However, buffer is an alkali and will also raise the pH level. Acid, which is used to lower pH, also lowers total alkalinity. The trick is, therefore, to raise the total alkalinity artificially high so that when the acid is added, to lower the pH to the correct range, the total alkalinity is also reduced to the correct range.

Two acid types are used to lower pH. One is Hydrochloric Acid and the other is Sodium Bisulphate. Both will effectively lower the pH and total alkalinity. If using Hydrochloric Acid to lower pH, it is vital that it be diluted (one part of acid to ten parts of water) prior to adding to the pool. Note that the filter should be running during addition and at least for one hour afterwards to ensure adequate mixing. No other types of acid should ever be used for pH or total alkalinity adjustment.

CALCIUM

Calcium naturally occurs in water. Different areas of the Country have higher and lower levels of calcium in the water. The higher the calcium concentration in the water, the more prone the pool is to calcium leeching. When the pH is maintained between 7.2 and 7.4 the calcium is balanced in the water.

Calcium levels should be maintained between 80 – 120 parts per million.

If your swimming pool uses mineral salts including magnesium please advise your pool shop when checking the pool hardness levels. A pool shop testing a sample of your pool water for total hardness will measure both magnesium and calcium present in the water as both of these come from the same family in chemical terms. This will result in far higher readings than expected. Please ensure the pool shop runs the test for calcium hardness as opposed to total hardness.

When the pH rises above 7.4, calcium begins to leech out of the water and cling to the swimming pool surface. The higher the pH is allowed to go, the more pronounced the calcification can become. Obviously, the problem occurs more often in areas with higher natural concentrations of calcium in the water (also known as hard water).

All that is required for calcium to fall out of solution creating a layer of scale is a pH of 7.5 or higher and calcium hardness over 150ppm. The higher the levels, the more pronounced the problem will be. The current guidelines being used for adding calcium to water are based on concrete pool guidelines. There should really be no reason why you should add Calcium Chloride to your water for a Leisure Pools Composite Armour™ swimming pool.

If a swimming pool is exposed to high pH levels, then an inconsistent discolouration below the waterline can occur. This whitening is due to calcium leeching from the pool water and clinging to the walls, steps and floor of the pool. It can be seen as a streak or solid area and is especially noticeable when the water level is lowered and the calcium dries.

If the swimming pool is exposed to high pH levels and a discolouration starts to occur, the problem can be treated in the early stage, say 1 to 3 months, with a chemical solution. First, the pH must be lowered to 6.5. Then treat the swimming pool with Muriatic Acid and or calcium treatments available at your local pool supply store. Muriatic Acid refers to atechnical grade of Hydrochloric Acid (HCI).

If the pool is equipped with a heater, heat pump etc. a bypass should be installed to isolate the unit(s) during the treatment to not damage the exchangers. Any other items that may be damaged from an extended low pH environment should also be removed or isolated. Once the problem is controlled, restore the pH to 7.2 to 7.4 and be sure to maintain it between these levels so the problem does not re-appear.

If the swimming pool is maintained with very high pH over a period of time, longer than 3 months then the problem can turn severe. The calcium begins to combine with the pool chlorine producing a chemical salt known as Calcium Chloride.

This is shown as CaCl2 and is the combination of calcium and chlorine. This salt attaches itself to the pool surface and causes the surface to appear significantly lighter especially when dehydrated. In advanced cases the Calcium Chloride is so bad that the pool even when hydrated (full of water) still shows the whitening.

If the pool has advanced Calcium Chloride but the gel coat returns to normal when hydrated then the pool can be treated using a chemical solution outlined above. It will take up to 6 months to allow the treatment to totally dissolve the Calcium Chloride, so it is best done over winter months. The pool will become more acidic, so it is not recommended for swimming.

If the gel coat has severe damage by the salt (Calcium Chloride) and it is visible when hydrated, then the solution is to remove the salt from the surface of the pool. To date, we have not been able to identify a chemical solution for the salt removal. As a result, the surface needs to be buffed and polished to firstly remove the salt build up and then to restore the lustre of the pool surface. It is however very important that you speak with your builder before draining the pool (see the section below on Not Emptying Your Swimming Pool).

Please note that some areas of the country have inherently high naturally occurring calcium levels. In these areas, we would suggest that you incorporate a stain and scale treatment as a part of general maintenance. Make sure to discuss this with your water care professional for the suggestion of type.

SANITISER

Chlorine is the most commonly used water sanitiser in the world. There are many forms of this highly effective product, including:

- Granular Chlorine (Calcium Hypochlorite) Granular Chlorine can raise calcium levels (see above);
- Liquid Chlorine (Sodium hypochlorite);
- Stabilised chlorine (chlorine in two forms "dichlor" granular chlorine approximately 60% active and "trichlor" slow dissolving tablets approximately 90% active);
- Salt water chlorinators these units produce chlorine through electrolysis of salt in the pool water.

Whatever form of chlorine you use, for it to work requires the pH to be in the correct range and sufficient quantities of chlorine. It is recommended that free chlorine levels are maintained between 1 to 2 parts per million. Chlorine levels should not exceed 5 parts per million as this can damage the Leisure Pools Composite Armour™ swimming pool.

To check Free Available Chlorine, use a DPD test kit.

STABILISER

Ultra-violet light attacks chlorine. Stabilizing pool water involves adding the chemical Cyanuric Acid to reduce the amount of chlorine destroyed by sunlight. Up to 5 parts per million of free available chlorine can be destroyed in three hours in strong sunlight.

For health and financial reasons, it is important to overcome this effect as much as possible. Stabilizing the water is strongly recommended in all outdoor pools. For the initial stabilizing of a new pool, Cyanuric Acid should be added to achieve the recommended level of 30 to 50 parts per million.

Stabiliser is lost through splash out and backwashing of the filter, and so will need to be replaced, especially during the swimming season. To do this it is necessary to first test for residual levels in the water. A water professional will be able to test the water in your pool and tell you how much stabiliser to add.

As you only need stabiliser in warmer months, adjust the level at the beginning of the swimming season and check it every few months during the season. Of course, if you have to pump out water or lose a lot through splash out and backwashing, more frequent testing and adjusting will be required.

CHEMICAL ADDITIONS

As a general rule, you are far better off adding small amounts of chemicals, running the filter and testing the effect after several hours. Attempting large chemical changes by adding large amounts of chemicals can result in big problems.

WHEN ADDING OR DILUTING CHEMICALS TO THE POOL, ALWAYS REMEMBER TO NEVER MIX CHEMICALS WITH ANY OTHER CHEMICAL. ALWAYS ADD CHEMICALS TO WATER - NEVER WATER TO CHEMICALS.

EXPLOSIONS HAVE BEENKNOWN TO OCCUR RESULTING IN INJURY OR DEATH.

DO NOT EMPTY YOUR SWIMMING POOL

It is critical that you do not empty your swimming pool or lower the level of the swimming pool water below the skimmer box; to do so will void your Lifetime Structural Warranty.

Leisure Pools Composite Armour™ swimming pools are designed to be a membrane in the ground between the earth and the water. To remove the support of either, the earth or part of the water will place enormous strain on the structural integrity of the Leisure Pools Composite Armour™ swimming pool resulting in possible damage to the structure of the shell.

Emptying or lowering the water below the skimmer box should only be done under the supervision of your pool builder. If in doubt, contact the manufacturer, Leisure Pools for advice.

If you empty your Leisure Pools Composite Armour™ swimming pool without the supervision of a Leisure Pools manufacturing representative and damage occurs, your swimming pool will not be covered by the Leisure Pools Warranty.

STANDPIPE / SUMP TUBE

Your Leisure Pools Composite Armour™ swimming pool may have been installed with a standpipe/sump tube. This is a pipe that travels to the bottom of the Leisure Pools Composite Armour™ swimming pool shell and enables you to measure the height of any underground water. The standpipe/sump tube will also enable you to use a pump to remove water around the pool shell should there be a build-up of groundwater around the pool.

Excessive groundwater around your swimming pool may cause structural damage to your Leisure Pools Composite Armour™ swimming pool that will not be covered by the Leisure Pools Warranty.

DRAINAGE

It is important that when you are installing your swimming pool and undertaking any landscaping work that you keep in mind the drainage of surface water. You must ensure that surface water does not run towards your swimming pool but rather away from the swimming pool. You must install enough drainage to keep the area around your swimming pool free of heavy surface and sub-surface water.

Excessive water around your swimming pool may cause structural damage to your Leisure Pools Composite Armour™ swimming pool that will not be covered by the Leisure Pools Warranty.

MODIFICATIONS / REPAIRS TO SWIMMING POOL

Leisure Pools Composite Armour™ swimming pools are relatively simple to repair should any damage occur.

A certified Leisure Pools technician can only undertake repairs on a Leisure Pools swimming pool. Should you have any repair issues please contact your Leisure Pools dealer directly. To have repairs undertaken by someone not authorised by Leisure Pools may void your Lifetime Structural Warranty. Please note that all warranty claims must be received in writing and accompanied by supporting information including pictures.

WINTERISING

In some regions, it is perfectly okay to leave your pool running all year long.

In other colder climates, winterising your pool is highly recommended. To ensure proper winterising, you must first make sure that any rainwater, naturally drains away from your pool. Then a regiment using skimmer plugs and return plugs with a combination of blowing out the lines is used. Please follow your Leisure Pools Dealer recommendation for winterisation. This will vary due to climate.



FIBRE-REINFORCED COMPOSITE POOL LIFETIME STRUCTURAL WARRANTY

Leisure Pools and Spas Manufacturing Pty Ltd as trustee of the Leisure Pools and Spas Manufacturing Unit Trust (hereafter referred to as "Leisure Pools") does hereby warrant its Fibre-Reinforced Composite Pool only upon this express limited warranty to the original purchaser only on the following terms:

1. LIFETIME STRUCTURAL WARRANTY:

Leisure Pools warrants the structural soundness of its Fibre-Reinforced Composite Pool against water loss due to defects in workmanship and materials for the lifetime of the original purchaser of the Fibre-Reinforced Composite Pool, or such shorter time as a Court may determine to be fair and reasonable.

Lifetime is defined to mean not less than 35 years.

2. LIFETIME STRUCTURAL OSMOSIS WARRANTY:

Leisure Pools warrants the structural soundness of its Fibre-Reinforced Composite Pool against water loss due to osmosis caused by defects in workmanship and materials for the lifetime of the original purchaser of the Fibre-Reinforced Composite Pool, or such shorter time as a Court may determine to be fair and reasonable.

Lifetime is defined to mean not less than 35 years.

3. EXCLUSIONS TO LIFETIME STRUCTURAL WARRANTY:

This limited warranty is void if:

- (a) The purchaser does not return a completed Warranty Card to Leisure Pools within 6 months of delivery of the Fibre- Reinforced Composite Pool; or
- **(b)** the Fibre-Reinforced Composite Pool is damaged or altered as a result of acts of nature including but not limited to earthquake, ground movement, storm or flood, inadequate site drainage, excessive hydrostatic pressure, ground water, underground springs, underground obstructions, tree roots, heavy water flow into the Fibre-Reinforced Composite Pool; or
- (c) the Fibre-Reinforced Composite Pool is not installed in accordance with Leisure Pools Installation Manual (refer to Leisure Pools for the Installation Manual for installation requirements); or
- (d) the Fibre-Reinforced Composite Pool is not installed level; or
- (e) the Fibre-Reinforced Composite Pool is not installed in accordance with Leisure Pools engineer's specification; or
- (f) the Fibre-Reinforced Composite Pool is not installed by an authorised Leisure Pools dealer; or
- (g) the Fibre-Reinforced Composite Pool has been subject to any alteration, neglect, misuse or abuse; or
- **(h)** the Fibre-Reinforced Composite Pool is emptied to a level less than the skimmer box or by more than 30% of the water capacity of the pool (whichever is the lesser) without the written approval of Leisure Pools; or
- (i) the Fibre-Reinforced Composite Pool is allowed to over flow with water; or
- (j) the purchaser does not comply with the Leisure Pools Handbook; or
- (k) the purchaser does not keep a monthly written record of the Chlorine, Free Chlorine, pH, Total Alkalinity and Calcium Hardness (calcium hardness is to be tested by a pool shop every 6 months) levels of the water in the Fibre-Reinforced Composite Pool; or

- (I) the purchaser fails to keep the pH level of the water between 7.2 and 7.4, total alkalinity of the water between 80 to 120 parts per million; or
- (m) the water chemistry in the Fibre-Reinforced Composite Pool is allowed to get outside of standard operating water conditions causing damage to the surface of the Fibre-Reinforced Composite Pool; or
- (n) the customer does not notify Leisure Pools or a Leisure Pools dealer in writing within 7 days of becoming aware of a potential structural warranty claim; or
- **(o)** the customer does not provide Leisure Pools or its agents or sub-contractors access to the Fibre-Reinforced Composite Pool during normal business hours.

This warranty does not cover water loss due to failure of pipe fittings, inlet fittings, outlet fittings, solar connections, manifold, skimmer, hydrostatic valve relief, light fittings or anything connected with the pool.

The manufactured product, Aquaguard® XH Gelcoat is not recommended for use in elevated temperature pool or spa applications where the surface finish will be subjected to continuous, long term exposures to treated pool water above 32 degrees celcius.

This warranty does not cover the coping (top edge around the perimeter of the swimming pool) of the Fibre-Reinforced Composite Pool. Leisure Pools recommends that you cover the coping of the swimming pool with concrete, pavers, tiles or other suitable covering subject to the conditions.

This warranty does not cover any equipment used in connection with the Fibre-Reinforced Composite Pool or any other accessories supplied or any surrounds including but not limited to decks, concrete, wood, masonry or any other surround around the Fibre-Reinforced Composite Pool.

4. WARRANTY CLAIM

Leisure Pools in its sole discretion will determine if the alleged warranty claim is due to or from a defect in workmanship or materials or alternatively whether the warranty claim is because of the actions or non-action by the installer, customer or some other cause.

If Leisure Pools determines that the warranty claim is because of defects in workmanship or materials Leisure Pools reserves the right to repair or replace the Fibre-Reinforced Composite Pool. In the event Leisure Pools chooses to replace the Fibre-Reinforced Composite Pool this limited warranty does not include removal or installation of a replacement Fibre-Reinforced Composite Pool.

In the event Leisure Pools chooses to repair the Fibre-Reinforced Composite Pool it will repair it so that it can retain water. Any warranty repairs may require modification to the Fibre-Reinforced Composite Pool or texture of the Fibre- Reinforced Composite Pool.

5. DISCLAIMERS

Leisure Pools shall in no event be liable for any personal injury, property damage, direct, indirect, special, incidental or consequential damage or losses of any kind or nature arising from or related to the performance or supply of the Fibre- Reinforced Composite Pool. The liability of Leisure Pools under this warranty shall not exceed the original amount paid for the Fibre-Reinforced Composite Pool.

6. LIMITATIONS

This limited warranty takes the place of all other warranties, express or implied, warranties of merchantable quality and fitness for any particular purpose. All previous representations, understandings and warranties in respect of the Fibre- Reinforced Composite Pool are superseded by this limited warranty and are of no effect. The limited warranty is to be interpreted in accordance with the laws of Queensland Australia.

7. TRANSFER OF WARRANTY

Leisure Pools will authorise the transfer of the Warranty within 5 years of the original purchase of the Fibre-Reinforced Composite Pool. In order to validly transfer the Warranty Leisure Pools is to be notified in writing of the change of ownership of the swimming pool and be provided with the new owner's name, address, telephone and e-mail details. A valid transfer will not occur until the new owner receives from Leisure Pools a New Leisure Pools Swimming Pool Handbook and Warranty. The transfer must occur within 1 month of the change of ownership of the swimming pool.

14



PLEASE KEEP RECORDS OF YOUR WATER TESTING TO MAINTAIN YOUR LIFETIME STRUCTURAL WARRANTY

Date	рН	Total Alkalinity	Free Available Chlorine	Calcium Hardness	Comments



PLEASE KEEP RECORDS OF YOUR WATER TESTING TO MAINTAIN YOUR LIFETIME STRUCTURAL WARRANTY

Date	рН	Total Alkalinity	Free Available Chlorine	Calcium Hardness	Comments



PLEASE KEEP RECORDS OF YOUR WATER TESTING TO MAINTAIN YOUR LIFETIME STRUCTURAL WARRANTY

Date	рН	Total Alkalinity	Free Available Chlorine	Calcium Hardness	Comments



CALL 1300-SPLASH (1300 775 274) For your closest Leisure Pools Dealer